

# ALLENTOWN'S BRASS & SWIVEL HOSE COUPLINGS

## Brass Hose Couplings — 1" through 1<sup>5</sup>/<sub>8</sub>"

Part Numbers			
Size	Female Half	Male Half	Coupling Set
1"	23-513	23-514	23-700
1 <sup>1</sup> / <sub>4</sub> "	23-517	23-518	23-702
1 <sup>1</sup> / <sub>2</sub> "	23-519	23-520	23-703
1 <sup>5</sup> / <sub>8</sub> "	23-521	23-522	23-704

Allentown's standard for over 80 years with rounded threads for ease of installation and compact design so it won't catch when hose is pulled around job site.



## Swivel Hose Couplings — 1<sup>1</sup>/<sub>4</sub>" through 2"

Part Numbers				
Size	Female Sleeve	Male Sleeve	Swivel Nut	Coupling Assembly
1 <sup>1</sup> / <sub>4</sub> "	23-203	23-200	23-206	23-770
1 <sup>1</sup> / <sub>2</sub> "	23-204	23-201	23-206	23-771
1 <sup>5</sup> / <sub>8</sub> "	23-205	23-202	23-206	23-772
2" with brass nut	23-853	23-852	23-224	23-781
2" with aluminum nut	23-853	23-852	23-850	23-866

Popular coupling with union-style swivel nut. Male and female sleeves made from strong, lightweight ZA alloy. Not available for 1" hose.



## Flanged Couplings

Flanged Hose Ends & Snap Couplings			
Size	Flanged Hose End Part #	Snap Coupling with Gasket	Gasket
1"	23-633	23-128 (2" coupling)	23-129 (2" gasket)
1 <sup>1</sup> / <sub>4</sub> "	23-634	23-631 (3" coupling)	23-632 (3" gasket)
1 <sup>1</sup> / <sub>2</sub> "	23-636	23-631 (3" coupling)	23-632 (3" gasket)
1 <sup>5</sup> / <sub>8</sub> "	23-637	23-631 (3" coupling)	23-632 (3" gasket)
2"	23-630	23-631 (3" coupling)	23-632 (3" gasket)
2 <sup>1</sup> / <sub>2</sub> "	23-627	23-625 (4" coupling)	23-624 (4" gasket)

Flanged couplings are similar to Hevi-Duty or Grooved type couplings used in wet-process applications. Rotary guns like the Piccola and GRH-610 have a flanged outlet. The snap coupling and gasket complete the connection.

